

TYM T273



TYM
TRACTORS

p.0800 887 337
www.tym.co.nz



ITEM	REMARK
ENGINE	
Manufacturer	Mitsubishi
Model	S3L2
Engine HP(kw) - Gross	27 (19.8)
PTO HP(kw)	20.7 (15.4)
Rated engine speed	2,700
Number of cylinders	3
Displacement-cu.in. (cc)	80.4 (1318)
Air cleaner	Dual Dry
ELECTRICAL SYSTEM	
Alternator	12V, 50A
FUEL SYSTEM	
Type	Indirect Fuel Injection
DRIVETRAIN	
Transmission type	HST
Number of speeds	Infinite / 2 Range
Max traveling speed, mph (km/h)	10.5 (17)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	N/A
HYDRAULIC SYSTEM	
Pump (type)	Dual Gear Pump
Implement pump cap.gpm (L/min)	5.0 (18.9)
Steering pump cap. gpm (L/min)	2.6 (10)
Maximum total flow gpm (L/min)	7.6 (28.9)
Category, 3 point hitch	Cat.I
Hitch lift capacity, lb. (kg)	1534 (700)
Hitch lift capacity at 24 inches behind link ends, lb(kg)	1102 (500)
Lift control type	Position
Joy stick valve	standard
No. of standard remote valves-option	1
PTO	
Type	Independent
Control	Electric/Hydro
Mid (rpm)-option	2000
Rear (rpm)	540
Shaft Diameter in. (mm)	1 3/8 (35)
CAPACITIES	
Fuel Tank, US gal. (L)	6.6 (25)
Cooling System U.S. qt. (L)	9.3 (8.8)
Crankcase (with filter) U.S. qt. (L)	6.0 (5.7)
Trans. & Hydr. System, U.S.gal. (L)	9.5 (36)
Front Axle qt. (L)	8.6 (8.2)
DIMENSIONS(with standard tires)	
Overall length, in. (mm) with 3P	107.8 (2740)
Overall width, in. (mm)	52.8 (1342)
Wheelbase, in. (mm)	58.3 (1480)
Height to top of ROPS, in. (mm)	97.2 (2470)
Min. Ground Clearance, in (mm)	7.71 (196)
Min. Turning Radius, in (mm) with brakes	98.5 (2502)
Min. Turning Radius, in (mm) w/o brakes	105.5 (2682)
STANDARD TIRES	
Front (R1)	
Rear (R1)	
Front (R4)	23x8.5-12 R4
Rear (R4)	12x16.5 R4
ROLL-OVER PROTECTIVE STRUCTURES	
Standard	ROPS
WEIGHT	
Total weight ,lb (kg)	2028 (920)