

TYM T353 HST



TYM

TRACTORS

P: 0800 TYM NZL

E: dave@powerturf.co.nz



ENGINE	Mitsubishi
Model	S4L2
Engine HP(kw) - Gross	35(25.7)
PTO HP(kw)	26(19.1)
Rated engine speed	2700
Number of cylinders	4
Displacement-cu.in. (cc)	107.3(1758)
Air cleaner	Dual Dry
ELECTRICAL SYSTEM	
Alternator	12V, 50A
FUEL SYSTEM	
Type	Indirect Fuel Injection
DRIVETRAIN	
Transmission type	HST
Number of speeds	Infinite/3 Range
Max traveling speed, mph (km/h)	16.1(26)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	N/A
HYDRAULIC SYSTEM	
Pump (type)	Dual Gear Pump
Implement pump cap.gpm (L/min)	6.3(23.9)
Steering pump cap. gpm (L/min)	4.6(17.3)
Maximum total flow gpm (L/min)	10.9(41.2)
Category, 3 point hitch	I
Hitch lift capacity, lb. (kg)	2646(1200)
at 24 inches behind link ends, lb(kg)	1764(800)
Lift control type	Position
Joy stick valve	standard
No. of standard remote valves-option	1
PTO	
Type	Independent
Control	Electric/Hydro
Mid (rpm)-option	2000
Rear (rpm)	540
Shaft Diameter in. (mm)	1 3/8(35)
CAPACITIES	
Fuel Tank, U.S. gal. (L)	9.0(34)
Cooling System U.S. qt. (L)	7.4(7)
Crankcase (with filter) U.S. qt. (L)	6.0(5.7)
Trans.& Hydr. System, U.S.gal. (L)	9.25(35)
Front Axle qt. (L)	8.7(8.2)
DIMENSIONS (with standard tires)	
Overall length, in. (mm) with 3P	130.5(3315)
Overall width, in. (mm)	52(1320)
Wheelbase, in. (mm)	66.1(1680)
Height to top of ROPS, in. (mm)	94.4(2400)
Min. Ground Clearance, in (mm)	13.8(350)
Min. Turning Radius, in (mm) with brakes	94.4(2400)
Min. Turning Radius, in (mm) w/o brakes	116(2950)
STANDARD TIRES	
Front	7.0-16 R1
Rear	11.2-24 R1
Front	27-10.5-15 R4
Rear	12.5-20 R4
ROLL-OVER PROTECTIVE STRUCTURES	
Standard	ROPS
WEIGHT	
Total weight ,lb (kg)	3065(1390)