

TYM T603



TYM

TRACTORS

FOLDABLE ROPS

-Foldable ROPS lets you operate under low-roof ceiling and it is convenient for storage



ENGINE	Caterpillar
Model	C2.2T
Engine HP(kw) - Gross	58 (43)
PTO HP(kw)	46.6(35)
Rated engine speed	2600
Number of cylinders	4
Displacement-cu.in. (cc)	135.2(2216)
Air cleaner	Dual Dry
ELECTRICAL SYSTEM	
Alternator	12V, 65A
FUEL SYSTEM	
Type	Indirect Fuel Injection
DRIVETRAIN	
Transmission type	Sync/Shuttle
Number of speeds	24/F 24/R
Max traveling speed, mph (km/h)	22(35.5)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Dry single plate
HYDRAULIC SYSTEM	
Pump (type)	Dual gear pump
Implement pump cap.gpm (L/min)	10.5(39.6)
Steering pump cap. gpm (L/min)	4.7(17.6)
Maximum total flow gpm (L/min)	15.1(57.2)
Category, 3 point hitch	II
Hitch lift capacity, lb. (kg)	4270(1937)
at 24 inches behind link ends, lb(kg)	2528(1147)
Lift control type	Position/Draft
Joy stick valve	standard
No. of standard remote valves-option	3
PTO	
Type	Independent
Control	Electric/Hydro
Mid (rpm)-option	N/A
Rear (rpm)	540 / 1000
Shaft Diameter in. (mm)	1 3/8 (35)
CAPACITIES	
Fuel Tank, U.S. gal. (L)	18.48(70)
Cooling System U.S. qt. (L)	9.5 (9)
Crankcase (with filter) U.S. qt. (L)	7.1 (6.7)
Trans.& Hydr. System, U.S.gal. (L)	11(42)
Front Axle qt. (L)	17.4(16.5)
DIMENSIONS(with standard tires)	
Overall length, in. (mm) with 3P	146.5(3722)
Overall width, in. (mm)	71.5 (1817)
Wheelbase, in. (mm)	83 (2100)
Height to top of ROPS, in. (mm)	101.9(2590)
Min. Ground Clearance, in (mm)	17.9 (455)
Min. Turning Radius, in (mm) with brakes	150.1(3815)
Min. Turning Radius, in (mm) w/o brakes	162.2(4120)
STANDARD TIRES	
Front	9.50-20 R1
Rear	14.9-28 R1
Front	12-16.5 R4
Rear	16.9-24 R4
ROLL-OVER PROTECTIVE STRUCTURES	
Standard	ROPS
WEIGHT	
Total weight ,lb (kg)	5204(2360)