

# TYM T723



**TYM**  
**TRACTORS**

**p.0800 887 337**  
**www.tym.co.nz**



ITEM	REMARK
<b>ENGINE</b>	
Manufacturer	Perkins
Model	1103C-33T
Engine HP(kw) - Gross	74 (55)
PTO HP(kw)	65 (48.5)
Rated engine speed	2,200
Number of cylinders	3
Displacement-cu.in. (cc)	201 (3,300)
Air cleaner	Dual Dry
<b>ELECTRICAL SYSTEM</b>	
Alternator	12V, 75A
<b>FUEL SYSTEM</b>	
Type	Direct Fuel Injection
<b>DRIVETRAIN</b>	
Transmission type	Sync/Shuttle
Number of speeds	24/F 24/R
Max travelling speed, mph (km/h)	19.5 (31.5)
Brakes	Wet Disc
Steering	Hydrostatic
Clutch	Drv single plate
<b>HYDRAULIC SYSTEM</b>	
Pump (type)	Dual gear pump
Implement pump cap.gpm (L/min)	11.1 (42)
Steering pump cap. gpm (L/min)	4.8 (18)
Maximum total flow gpm (L/min)	15.9 (60)
Category, 3 point hitch	II
Hitch lift capacity, lb. (kg)	4,330 (1,964)
Hitch lift capacity at 24 inches behind link ends, lb(kg)	3,333 (1,512)
Lift control type	Position/Draft standard
Joy stick valve	standard
No. of standard remote valves-option	3
<b>PTO</b>	
Type	Independent
Control	Electric/Hydro
Mid (rpm)-option	N/A
Rear (rpm)	540/540E(750)
Shaft Diameter in. (mm)	1 3/8 (35)
<b>CAPACITIES</b>	
Fuel Tank, US gal. (L)	19 (72)
Cooling System U.S. qt. (L)	10 (9.5)
Crankcase (with filter) U.S. qt. (L)	7.4 (7)
Trans.& Hydr. System, U.S.gal. (L)	12.4 (47)
Front Axle qt. (L)	17.2 (16.3)
<b>DIMENSIONS(with standard tires)</b>	
Overall length, in. (mm) with 3P	149 (3,786)
Overall width, in. (mm)	77.6 (1,970)
Wheelbase, in. (mm)	83.2 (2,114)
Height to top of ROPS, in. (mm)	102 (2,595)
Min. Ground Clearance, in (mm)	18.3 (466)
Min. Turning Radius, in (mm) with brakes	142.5 (3,620)
Min. Turning Radius, in (mm) w/o brakes	167 (4,240)
<b>STANDARD TIRES</b>	
Front (R1)	11.2-24
Rear (R1)	16.9-30
Front (R4)	-
Rear (R4)	-
<b>ROLL-OVER PROTECTIVE STRUCTURES</b>	
Standard	CAB
<b>WEIGHT</b>	
Total weight ,lb (kg)	5,771 (2,618)